



Ventilated Work Benches

DuraBench Work Stations may be utilized in conjunction with most major brands of properly sized dust collection systems to provide additional ventilated work areas for hand grinding, polishing, sanding, cutting or other hand-held shop operations.

Fiberglass work surfaces, leveling screws, duct connection ports, and a unique internal baffle assembly provide uniform surface velocities for worker protection.

Standard Features

- **Heavy Duty Sheet Steel Construction**
 - 10 and 12 Gauge steel for extra strength
- **Fibergrate Fiberglass Work Deck**
 - Exceptional strength-to-weight ratio. Non-conductive and slip resistant
- **Structural Legs**
 - Tapered and strong with height adjustment bolts
- **Tapered Table Bottoms**
 - Ergonomic design for comfortable sitting or standing positions
- **Uniform Surface Velocities**
 - Unique internal baffle assembly assures even distribution of downward air
- **Urethane Mastic Coating**
 - Durethane DTM by PPG chemically resistant and extremely durable. Provides excellent corrosion resistance and has superior color and gloss retention.
- **3 Foot—10 Foot Widths**
 - Multiple widths for any application with custom widths and depths available.

HIGHLIGHTS



Single or Multiple
Discharge Duct
Connection Ports



Side Panels, Back Panels and Lighting
Options



Specifications

Deck Size	CFM Requirement Based on 300 FPM at the Deck
24" x 36"	1,440
24" x 48"	1,920
24" x 60"	2,400
24" x 72"	2,880
24" x 84"	3,360
24" x 96"	3,840
24" x 108"	4,320
24" x 120"	4,800
24" x 132"	5,280
24" x 144"	5,760
36" x 36"	2,160
36" x 48"	2,880
36" x 60"	3,600
36" x 72"	4,320
36" x 84"	5,040
36" x 96"	5,760
36" x 108"	6,480
36" x 120"	7,200
36" x 132"	7,920
36" x 144"	8,640